

## 24kW High Frequency Charger



FastCharge EKT's highly efficient lithium battery charger, reliable and robust and CAN-BUS ready.

### Technical Specifications

Technical Data										
24000W	INPUT					OUTPUT				
Model	AC Voltage	AC Phase	Rated Frequency	Input Current(Max)	Power factor	Conversion efficiency	Rated output voltage	Dimension(mm)	Weight	Cooling mode
48V250A	AC220V±15%	Three Phase four wire	50/60Hz	<=41A	≥0.99	≥0.92	57.6V	378x428x791	55kg	Air cooling
80V250A	AC220V±15	Three Phase four wire	50/60Hz	<=63A	≥0.99	≥0.92	87.6V	378x428x791	55kg	Air cooling
80V250A	AC380V±15%	Three Phase four wire	50/60Hz	<=36.2A	≥0.99	≥0.92	87.6V	378x428x791	55kg	Air cooling
80V250A	AC480V±15	Three Phase four wire	50/60Hz	<=28.6A	≥0.99	≥0.92	87.6V	378x428x791	55kg	Air cooling
96V200A	AC380V±15%	Three Phase four wire	50/60Hz	<=36A	≥0.99	≥0.92	108V	378x428x791	55kg	Air cooling
153.6V150A	AC380V±15%	Three Phase four wire	50/60Hz	<=42.8A	≥0.99	≥0.92	172.8V	378x428x791	55kg	Air cooling

TAKE BACK THE POWER!

[www.fastchargeaust.com.au](http://www.fastchargeaust.com.au)

P: 1800 084 099

service@fastchargeaust.com.au